



ES-5700

Clean, Reliable, Affordable Energy



CLEAN, RELIABLE POWER ON DEMAND

Bloom Energy's ES-5700 delivers clean power that reduces emissions and energy costs. The modular architecture enables the installation to be tailored to the actual electricity demand, with a flexibility to add servers as the load increases. The ES-5700 actively communicates with Bloom Energy's network operations centers so system performance can be monitored and maintained 24 hours per day, 365 days per year.

INNOVATIVE TECHNOLOGY

Utilizing patented solid oxide fuel cell (SOFC) technology, the ES-5700 produces combustion-free power at unprecedented efficiencies, meaning it consumes less fuel and produces less CO₂ than competing technologies. Additionally, no water is needed under normal operating conditions.

ALL-ELECTRIC POWER

The ES-5700, which operates at a very high electrical efficiency, eliminates the need for complicated and costly CHP systems. Combining the standard electrical and fuel connections along with compact footprint and sleek design, the ES-5700 is the most deployable fuel cell on the market.

CONTROLLED AND PREDICTABLE COST

By providing efficient on-site power generation, the economic and environmental benefits are central to the ES-5700 value proposition. Bloom Energy customers can lock in their long term energy costs and mitigate the risk of electricity rate increases. The ES-5700 has been designed in compliance with a variety of safety standards and is backed by a comprehensive warranty.

About Bloom Energy

Bloom Energy is making clean, reliable energy affordable. Our unique on-site power generation systems utilize an innovative fuel cell technology with roots in NASA's Mars program. By leveraging breakthrough advances in materials science, Bloom Energy systems are among the most efficient energy generators, providing for significantly reduced operating costs and dramatically lower greenhouse gas emissions. Bloom Energy Servers are currently producing power for many Fortune 500 companies including Apple, Google, Walmart, AT&T, eBay, Staples, as well as notable non-profit organizations such as Caltech and Kaiser Permanente.

Headquarters:

Sunnyvale, California

For More Information:

www.bloomenergy.com

ES-5700

Technical Highlights

Outputs

| | |
|---------------------------------|-----------------------|
| Nameplate power output (net AC) | 210 kW |
| Base load output (net AC) | 200 kW |
| Electrical connection | 480 V, 3-phase, 60 Hz |

Inputs

| | |
|---------------------|------------------------------|
| Fuels | Natural gas, directed biogas |
| Input fuel pressure | 15 psig |
| Water | None during normal operation |

Efficiency

| | |
|---|---------------------|
| Cumulative electrical efficiency (LHV net AC) | 52-60% |
| Heat rate (HHV) | 6,295-7,264 Btu/kWh |

Emissions

| | |
|-------------------------------------|--|
| NO _x | < 0.01 lbs/MWh |
| SO _x | Negligible |
| CO | < 0.10 lbs/MWh |
| VOCs | < 0.02 lbs/MWh |
| CO ₂ @ stated efficiency | 735-849 lbs/MWh on natural gas; carbon neutral on directed biogas |

Physical Attributes and Environment

| | |
|-------------------|------------------------|
| Weight | 19.4 tons |
| Dimensions | 26' 5" x 8' 7" x 6' 9" |
| Temperature range | -20° to 45° C |
| Humidity | 0% - 100% |
| Seismic vibration | IBC site class D |
| Location | Outdoor |
| Noise | < 70 dBA @ 6 feet |

Codes and Standards

| |
|---|
| Complies with Rule 21 interconnection and IEEE1547 standards |
| Exempt from CA Air District permitting; meets stringent CARB 2007 emissions standards |
| Product listed by Underwriters Laboratories Inc. (UL) to ANSI/CSA America FC 1-2004 |

Additional Notes

| |
|---|
| Access to a secure website to monitor system performance & environmental benefits |
| Remotely managed and monitored by Bloom Energy |
| Capable of emergency stop based on input from the site |



Bloom Energy Corporation
1299 Orleans Drive
Sunnyvale CA 94089
T 408 543 1500
www.bloomenergy.com